

# Siting observers in huge terrains stored in external memory

Salles V. G. de Magalhães<sup>1</sup>, Marcus V. A. Andrade<sup>1</sup>, and W. Randolph Franklin<sup>2</sup>

Universidade Federal de Viçosa, Viçosa, MG, Brasil  
Rensselaer Polytechnic Institute, Troy, NY, USA  
`{smagalhaes,marcus}@dpi.ufv.br`  
`frankwr@rpi.edu`

**Abstract.** We present an algorithm and implementation for EMSite, which sites multiple (perhaps hundreds) of observers on a DEM terrain that is too large to store in internal memory. EMSite has been implemented in C++. Tests show it to use a median of 19% fewer observers to obtain the same joint visibility index (coverage) on huge terrains, compared to a naive partitioning of the terrain into subregions. This will permit more efficient positioning of facilities such as mobile phone towers, fire observation towers, and vigilance systems.

**Key words:** siting, terrain visibility, coverage, viewshed, line of sight, facilities positioning.

## 1 Introduction

Advances in remote sensing have produced large quantities of high resolution geographic data that require new Geographic Information Systems[10] (GISs) techniques to process.

The Earth's surface elevation (terrain) data is usually approximately represented by a digital elevation matrix (DEM) that stores the elevations of regularly sampled terrain points. Elevations of intermediate points are approximated using some interpolation process[5, 11]. This simple representation requires more space for very large datasets, even after compression, than is available in most computers' internal memory. Therefore we require efficient applications to process the data in external memory.

The design and analysis of algorithms to manipulate data in external memory needs to focus on optimizing the data transfer since this is much slower than internal memory access. The algorithm design goal is to minimize the number of external memory accesses since this is the dominant cost.

An important group of GIS applications on terrain concerns visibility, i.e., determining the set of points on the terrain are visible from some particular observer. The observer can be located at some height above the terrain. Applications include telecommunications, environmental planning, autonomous vehicle navigation, and military monitoring[6, 11, 12]. One important problem is the

positioning of a given number of facilities in order to optimally “cover the terrain”. These facilities may be radio, TV, internet or mobile phone towers, and monitoring towers[3, 13].

In this paper we present a solution to the multiple observer problem, i.e., a method to site facilities in terrain represented by huge elevation matrices that are stored in the external memory. This work extends Franklin[7, 8], which sites observers in terrain using internal memory.

## 2 Terrain Visibility

**Definition 1.** *A terrain represents a region of the earth’s surface. In the context of this paper, it is a scalar field over a square (in the relevant coordinate system) domain. The terrain’s value at any point is the elevation of the corresponding point of the earth’s surface above some reference ellipsoid called the geoid that represents sea-level. For this paper, terrain is represented by a matrix of elevation posts on a square grid, whose vertical and horizontal spacing is uniform either in distance, e.g., 30m, or in angle, e.g. 1 arc-second.*

Other representations such as triangular splines, or Triangulated Irregular Networks (TINs), are also common. Their implementation is more complicated, especially for operations such as line-of-sight. When only a coarse approximation to the terrain is needed, a TIN is compact. However, in this case, a DEM may be lossily compressed to an extremely small size. Indeed, by separating the abstract data structure, the grid, from the concrete implementation, the compression algorithm, the DEM is conceptually a better designed representation, while easier to implement, and apparently equally compact.

**Definition 2.** *An observer is a point in space from which we wish to see or communicate with other points in space, called targets. The usual notation for observer and target is  $O$  and  $T$ . The base points of  $O$  and  $T$  are the points on the terrain directly below  $O$  and  $T$ , respectively. They are denoted as  $O_b$  and  $T_b$ .  $O$  and  $T$  are each at height  $h$  above  $O_b$  and  $T_b$ .*

The possible generalization of having separate heights for the observer and target, while adding another degree of freedom to the experiments, does not seem to add anything new to the science of the problem. That is, earlier tests lead us to believe that our conclusions are general.

**Definition 3.** *The radius of interest,  $R$ , of  $O$  is the distance out to which it can see, in the absence of obstructions. E.g., if  $O$  is a radio transmitter,  $R$  is a function of the transmitter power and receiver sensitivity. For convenience,  $R$  is measured between  $O_b$  and  $T_b$  rather than between  $O$  and  $T$ , which is equivalent when  $h$  is much smaller than the radius of the earth.*

**Definition 4.**  *$T$  is visible from  $O$  iff  $|T_b - O_b| \leq R$  and there is no terrain point between  $O$  and  $T$  blocking the line segment, called the Line of Sight (LOS), between them; see Figure 1. In this Figure,  $T_1$  is visible from  $O$  but  $T_2$  is not.*




Fig. 1. Visibility queries using a line of sight

Determining whether or not some terrain blocks the LOS is non-trivial, and a subject of current research. The problem is that the terrain is defined only at the points, or posts, in the DEM, while the LOS in general passes between adjacent posts; see Figure 2. Indeed, the numbers in the DEM may not even be point elevations but rather averages over some areas.





Fig. 2. LOS threading between elevation posts

Therefore the terrain elevation must be interpolated along the LOS. The true elevation at an interpolation point might well be greater than the greatest adjacent post, or less than the smallest adjacent post. Small, apparently unimportant, changes in the interpolation algorithm might cause major changes in the targets' visibility. Consider Figure 3, showing the United States Geological Survey Lake Champlain West DEM, with the observer positioned on Mt Marcy, the highest point, and the curvature of the earth being ignored. In this example, interpolating by using the maximum adjacent post elevation instead of the minimum adjacent post elevation changes the visibility of one half of all the targets.

**Definition 5.** *The viewshed,  $v$ , of  $O$  is the set of base points whose corresponding targets are visible from  $O$ .  $V$  is stored as a bit matrix with the bits packed into the longest words that can be processed in one machine cycle.*

**Definition 6.** *The visibility index,  $\omega$ , of  $O$  is the number of targets with base points within the circle  $C$  of radius  $R$  centered at  $O_b$  that are visible from  $O$ .*



**Fig. 3.** Visibility of one-half of the terrain affected by LOS interpolation rule

Points with a large  $\omega$  are good candidate places to site observers in order to maximize the area of the terrain that is seen by at least one observer.  $\omega$ , which is simply the number of 1-bits in  $V$ , is commonly estimated by counting how many of a random sample of targets inside  $C$  are visible.

**Definition 7.** *The joint viewshed,  $\mathcal{V}$ , of a set of observers  $\mathcal{O} = \{O_i\}$  is the union of the individual viewsheds  $v_i$ , i.e., the bitwise-or of their bit matrices.*

**Definition 8.** *The joint visibility index,  $\Omega$ , of  $\mathcal{O}$  is the number of targets in the terrain that are visible from at least one observer in  $\mathcal{O}$ .  $\Omega$  may be normalized to be a percent of the terrain area.*

**Definition 9.** *Multi-observer siting means optimizing the locations of a set of observers, called siting, so that  $\Omega$  is as large as possible. This has important practical facilities-location applications, such as siting mobile phone towers, fire monitoring towers, and radar systems.*

The multi-observer siting problem is NP-hard[12], and can be reduced to classical set coverage optimization[4]. The set cover problem is this: Given a set  $S = \{s_i\}$  of sets, choose  $C = \{c_i\} \subset S$  such that  $\cup c_i = \cup s_i$  and  $|C|$  is minimized[2]. Informally, find the smallest number of sets  $s_i$  whose union is equal to the union of all the  $s_i$ .

This paper will present a heuristic approximate solution to the following NP-hard problem: to find the minimum number of observers to achieve a given terrain coverage, i.e., whose joint viewshed is at least a certain minimum fraction of the terrain area. Our solution can also be adapted to maximize the joint viewshed with a fixed number of observers.

### 3 The Site method

Since the observer siting problem is NP-hard, Franklin[6] presented Site, an approximate heuristic solution, to find a set of observers to cover the terrain. Site uses a greedy approach to select the set  $\mathcal{O} = \{O_i\}$  of observers from a much larger set  $\mathcal{P} = \{P_i\}$  of potential observers, together with their viewsheds. Initially  $\mathcal{O} = \{\}$ . At each step, the  $P_i$  that would most increase the joint viewshed of  $\mathcal{O}$  is inserted into  $\mathcal{O}$ . The details are as follows.

1. Estimate the visibility index of each point in the terrain  $M$ . More precisely, determine the points that have a certain minimum visibility index with a certain confidence level. This may be achieved by sampling random targets.
2. Compute  $\mathcal{P} = \{P_i\}$  as the set of points with the largest visibility indexes. E.g., with a typical  $M$  with  $|M| = 1\,442\,401$  (for a  $1201 \times 1201$  matrix of posts, the standard for a level-1 USGS DEM),  $|\mathcal{P}|$  might be 1000. However, do not select two points that are too close together, since their viewsheds will probably overlap considerably, and hence, one of them will be redundant.

3. Compute  $v_i$ , the viewshed of each  $P_i$ .  $v_i$  is that region of the terrain visible from an observer sited at  $P_i$ .  $v_i$  is conveniently stored as a bitmap.
4. Initialize  $\mathcal{O} = \{O_i\} = \{\}$ . This will accumulate the set of actual observers.  $\mathcal{O} \subset \mathcal{P}$ .
5. Initialize  $\mathcal{V}$ , the joint viewshed of  $\mathcal{O}$ , that is the union of the viewsheds of all the  $O_i$ , to all 0 bits.
6. Repeat the following until a termination condition is satisfied. Typical conditions include that  $|\mathcal{O}|$  reaches a certain maximum, or  $area(\mathcal{V})$  a certain minimum.
  - (a) Iterate through  $\mathcal{P}$  to find the  $P_i$  that would cause  $\mathcal{V}$  to increase the most. That involves repeatedly finding the area of the union of two bitmaps ( $\mathcal{V}$  and  $v_i$ ), which is very fast.
  - (b) Insert that  $P_i$  into  $\mathcal{O}$  and update  $\mathcal{V}$ .
  - (c) However, if it is desired that  $\mathcal{V}$  be a connected set, to enforce *intervisibility*, then do not pick a  $P_i$  that would cause the new  $\mathcal{V}$  to be disconnected.

### 3.1 Using Site on huge terrain

If the terrain is too large to be stored in internal memory, the obvious extension of Site is to simply subdivide the elevation matrix  $M$  into subregions  $M_i$  each small enough to fit into internal memory, and then use Site on each  $M_i$ . The problem is that the viewshed  $\mathcal{V}$  of a point may cross into several  $M_i$ . Even for a small radius of interest,  $\mathcal{V}$  may easily overlap four  $M_i$ . That is, visibilities on any particular  $M_i$  are affected by points not in that  $M_i$ . There are several possible solutions.

First, since this is only an approximate method, we might simply ignore the effect of viewsheds that cross into another  $M_i$  and work with truncated viewsheds. Since the effective viewsheds of observers near the edge of the  $M_i$  would be too small, those observers' visibility indexes would be underestimated and they might be excluded when it would be optimal to include them. The effect of this on the quality of the resulting set of observers would need to be determined empirically, but might be acceptable if the  $M_i$  are much larger than the viewsheds.

To illustrate this situation, see Figure 4 where the terrain was divided into four regions:  $M_1$ ,  $M_2$ ,  $M_3$  and  $M_4$  and a potential observer  $O$  close to  $M_2$ 's lower left corner is being considered. It is possible that  $O$ 's viewshed  $v$  is large, but, since  $v$  is split between  $M_{1\dots4}$ , the amount of  $v$  inside  $M_2$  is small. Therefore  $O$ , erroneously, might not be added to the set of potential observers for  $M_2$ .

Another limitation of this approach is that observers will not be sited optimally in  $M_1$  because the part of  $v$  in  $M_1$  will be ignored (because the  $M_i$  are being processed independently).

## 4 The EMSite method

EMSite (External Memory Site), our new method, extends the idea described above in Section 3.1 in order to consider the influence of observers sited near to




Fig. 4. Terrain subdivision into four subregions

the borders of the subregions. It also correctly computes the joint viewshed of any given set of observers while working within the available main memory and minimizing I/O.

The major idea is to add a band of width  $R$  around each region when subdividing the terrain into small subregions. During the processing of each subregion, observers will be sited only at points in the core region, not in the additional band. However, those observer's viewsheds can extend into the band. See Figure 5, where terrain subregion  $M_2$  has an additional band  $A$ . During  $M_2$ 's processing, observers may be sited only in  $M_2$  but their computed viewsheds may extend into  $A$ , and the viewshed portions in  $A$  will be properly used.

Another key to EMSite is the sophistication of the observer siting heuristics, which proceeds in two or more stages. The joint viewshed for the whole terrain is represented by a matrix  $\mathcal{V}$  stored in external memory. EMSite proceeds as follows.

1. Initialize  $\mathcal{V}$  by setting all points to be not visible (since no observers to see them have been sited yet).
2. For each subregion  $M_i$ :
  - (a) Execute Site in  $M_i$  to site a initial number of observers  $\mathcal{I}$ , e.g.,  $|\mathcal{I}| = 2$ . That means to find two observers that increase the joint viewshed as much as is possible.
  - (b) However, during this process note that (if  $i > 0$ ) some points in  $M_i$  are already visible by observers sited in  $M_j$  for  $j < i$ . That is, don't identify observers that are good for  $M_i$  when considered in isolation, but identify observers whose viewsheds cover parts of  $M_i$  that have not already been covered by observers sited in the earlier  $M_j$ .
  - (c) Compute  $\mathcal{I}$ 's joint viewshed as a bit matrix  $\mathcal{C}_i$  that may extend into  $M_i$ 's border zone, that is into other subregions.





Fig. 5. Additional band for  $M_2$

- (d)  $\mathcal{V} \leftarrow \mathcal{V}$  bitwise-or  $\mathcal{C}_i$
3. Now that an initial set of observers has been sited, process the regions again to fill in visibility gaps.
  4. Choose  $\delta$ , an amount by which any future observer that is sited will be required to increase the size of the joint viewshed.
  5. Sort  $\mathcal{M} = \{M_i\}$  by the size of the joint viewshed in each  $M_i$  from large to small. The goal is to start siting observers in regions that are easier to cover.
  6. For each  $M_i$  in sorted order, site more observers with **Site**, stopping when a new observer would add less than  $\delta$  new visible area to the joint viewshed.
  7. Stop when either the joint viewshed is the desired size, or the maximum number of observers is used.
  8. Otherwise, reduce  $\delta$  and go back to step 5.

Figure 4 graphically displays those stages. The radius of interest was chosen small to make the problem harder, since then more observers are needed. Since the first observers to be sited are the best observers, their viewsheds are complete circles. As seen in (c) and (d), the later observers to be chosen have incomplete viewsheds; their visibility indexes are less than 1.

## 5 Improvements to **Site**

We also improved the original method **Site** by changing the viewshed representation, originally a bit matrix of the same size as the terrain. Now, each viewshed is represented as a square bit matrix of side  $2R - 1$  where  $R$  is the observer



**Fig. 6.** EMSite stages: (a) Two observers are sited in each region. (b) The regions are sorted in decreasing order of their joint viewshed. (c) Partway through the process, more observers are sited in each region until the contribution of the last observer to the joint viewshed is smaller than a threshold. (d) The final result showing the desired joint visibility index.


radius of interest, together with a header describing the number of bytes in each viewshed line, the viewshed bounding-box coordinates in the original terrain,  $R$ , and the observer’s coordinates, both in the bounding-box and in the original terrain.

Since the viewsheds now use less storage, *Site*’s time and space resource requirements are significantly smaller.

## 6 Results

We implemented *EMSite* in C++. This is apparently the only observer siting method able to process data in external memory. We tested *EMSite* by comparing it to the simple external version of *Site*, described above in section 3.1, using terrain representing the northeast of Brazil — see Figure 7. The test data is from the NASA SRTM[9] as follows.

- Terrain 1: A  $4804 \times 4804$  block from northeast Brazil.
- Terrain 2: Another  $4804 \times 4804$  block from northeast Brazil. The elevation of the points around the center of the region was modified to be equal to 0. This was done to simulate a terrain with a center plane area surrounded by hills. This seemed to be a more difficult dataset to achieve a good joint visibility index on, and we wished to stress-test *EMSite*.



**Fig. 7.** Images representing the terrains used in the tests: Terrain 1 (a), Terrain 2 (b).

Table 1 presents the results obtained by *EMSite* and *Site* using several different values of desired joint visibility index  $\Omega$ , with observers’ and target’s heights of  $1m$  and  $15m$  above the ground. Also, it was used two different  $R$  (radii of interest): 100 and 250 points. Column  $\# Obs$  shows the number of observers

sited by each method. Column *EMSite Improv.* gives the improvement of EMSite compared to Site.

Both sets of terrain were subdivided into 16 subregions. Although each subregion size is about 44MB, it can't be processed in internal memory using the original Site because it needs to load several viewsheds into memory during the observer siting.

Terrain	R	Desired $\Omega$	EMSite # Obs	Site # Obs	EMSite Improv.
1	100	25%	363	402	11%
		50%	992	1074	8%
		75%	2810	2940	4%
		80%	3963	4057	2%
2	100	25%	221	344	36%
		50%	656	879	25%
		75%	1724	2305	25%
		80%	2294	3143	27%
1	250	25%	84	113	26%
		50%	291	338	14%
		75%	954	1073	11%
		80%	1574	1964	20%
2	250	25%	44	85	48%
		50%	179	237	24%
		75%	573	781	26%
		80%	789	1107	29%

**Table 1.** Comparison of the number of observers used by EMSite and Site to achieve the desired  $\Omega$ , with observers' and targets' heights 1 meter above the ground.

As one can see, EMSite can achieve the desired  $\Omega$  using a much smaller number of observers than Site. The median number of fewer observers is 25%.

In Table 2, the two methods were reevaluated with the observers and targets now positioned at 15m above the ground. Again, EMSite produced better results, using a much smaller number of observers for the same  $\Omega$ ; the median improvement is 18%.

Finally, Table 3 shows the results of tests considering higher desired  $\Omega$ . Notice that, in some cases, as for  $\Omega = 88\%$ , EMSite can be much better than Site using less than a half of observers to achieve the desired  $\Omega$ . In other cases, as for  $\Omega = 90\%$ , EMSite can succeed while Site can not.

Terrain	R	Desired $\Omega$	Site # Obs	EMSite # Obs	EMSite Improv.
1	100	25%	202	197	33%
		50%	428	408	5%
		75%	754	831	-10%
		85%	1 338	1 037	22%
2	100	25%	200	195	3%
		50%	416	401	4%
		75%	791	729	8%
		85%	1 239	1 017	18%
1	250	75%	166	137	17%
		90%	293	237	19%
2	250	75%	208	168	19%
		90%	257	210	18%

**Table 2.** Comparison of the number of observers used by EMSite and Site to achieve the desired  $\Omega$ , with observers' heights 15 meters above the ground.

Terrain	R	Desired $\Omega$	Site # Obs	EMSite # Obs	EMSite Improv.
1	250	80%	1 964	1 574	20%
		88%	11 866	5 424	54%
		90%	—	13 259	$\infty$

**Table 3.** Comparison of the number of observers used by EMSite and Site to achieve high  $\Omega$ . The observers' and targets' heights are 1m.

## 7 Conclusions and future work

This paper presented EMSite, which is able to site observers on huge terrain datasets that can not be stored in internal memory, and so need to be processed externally. The test results show that EMSite works well, and, compared with a straight adaptation of Site to process huge terrains, EMSite required up to 54% fewer observers, with a median of 19% fewer. This may lead to significant financial savings, example, by decreasing the number of mobile phone towers needed to cover a city.

The EMSite source code is available, [1].

Our next step is to adapt EMSite to site observers with a very large radius of interest, so that the terrain subregion including the band does fit into internal memory.

## 8 Notation summary

$O$  observer  
 $T$  target  
 $O_b$  observer's base point  
 $T_b$  target's base point  
 $h$  height of observer and target above terrain  
 $R$  radius of interest  
 $V$  viewshed  
 $\omega$  visibility index of an observer  
 $\mathcal{O}$  set of observers  
 $\mathcal{V}$  joint viewshed of a set of observers  
 $\Omega$  joint visibility index of a set of observers  
 $P$  potential observer  
 $\mathcal{P}$  set of potential observers  
 $M$  terrain  
 $\mathcal{I}$  initial set of observers

## Acknowledgement

This work was partially supported by FAPEMIG – the State of Minas Gerais Research Foundation – project APQ-00329-08 – HidroExt – Hidrology in terrains stored in external memory, and by CNPq – the Brazilian Research Council.

## References

1. Andrade, M.: EMSite code. <http://www.dpi.ufv.br/~marcus/projects/EMSite.htm> (2009)
2. Black, P.E.: Set cover. In Black, P.E., ed.: Dictionary of Algorithms and Data Structures [online]. U.S. National Institute of Standards and Technology (17 Dec 2004) <http://www.itl.nist.gov/div897/sqg/dads/HTML/setcover.html>, [accessed 19-Jan-2010].

3. Chaves, M.A.: Modelos digitais de elevação hidrologicamente consistentes para a bacia amazônica. Phd thesis, Universidade Federal de Viçosa, MG Brasil, Departamento de Engenharia Florestal (2002)
4. de Oliveira., N.V.: Problemas de coberturas de conjuntos, uma comparação numérica de algoritmos heurísticos. Tese de mestrado em engenharia de produção, Universidade Federal de Santa Catarina - UFSC (1999)
5. Felgueiras, C.A.: Modelagem numérica de terreno. In In G. Câmara, C. Davis, A.M.V.M., ed.: Introdução à Ciência da Geoinformação. Volume 1. INPE (2001)
6. Franklin, W.R., Ray, C.: Higher isn't necessarily better - visibility algorithms and experiments. In: 6th Symposium on Spatial Data Handling, Edinburgh, Scotland (1994) ISBN 2-540-43802-5.
7. Franklin, W.R.: Siting observers on terrain. In Richardson, D., van Oosterom, P., eds.: Advances in Spatial Data Handling: 10th International Symposium on Spatial Data Handling, Springer (2002) 109–120
8. Franklin, W.R., Vogt, C.: Tradeoffs when multiple observer siting on large terrain cells. In Riedl, A., Kainz, W., Elmes, G., eds.: Progress in spatial data handling: 12th international symposium on spatial data handling. Springer, Vienna (2006) 845–861 ISBN 978-3-540-35588-5.
9. Jet Propulsion Laboratory: Shuttle radar topography mission. <http://www2.jpl.nasa.gov/srtm> [accessed 30-Dec-2009] (2009)
10. Laurini, R., Thompson, D.: Fundamentals of Spatial Information Systems. Academic Press (1992)
11. Li, Z., Zhu, Q., Gold, C.: Digital Terrain Modeling - principles and methodology. CRC Press (2005)
12. Nagy, G.: Terrain visibility. Computers and Graphics **18** (1994) 763–773
13. Tarboton, D.G., Ames, D.P.: Advances in the mapping of flow networks from digital elevation data. In: World Water and Environmental Resources Congress. (2001) 107–111