

NSIGHT ECLIPSE EDITION

DG-06450-001 _v7.0 | August 2014

Getting Started Guide

TABLE OF CONTENTS

Chapter 1. Introduction	1
1.1. About Nsight Eclipse Edition	1
Chapter 2. New and Noteworthy	2
2.1. New in Nsight Eclipse Edition 6.5	2
2.2. New in Nsight Eclipse Edition 6.0	2
2.3. New in Nsight Eclipse Edition 5.5	4
Chapter 3. Using Nsight Eclipse Edition	6
3.1. Installing Nsight Eclipse Edition	6
3.1.1. Installing CUDA Toolkit	6
3.1.2. Mac OS X Additional Notes	6
3.2. Running Nsight Eclipse Edition	7
3.3. Creating a New Project	7
3.4. Importing CUDA Samples	8
3.5. Debugging CUDA Applications	9
3.6. Remote development of CUDA Applications	. 10
3.7. Debugging Remote CUDA Applications	. 13
3.8. Profiling CUDA applications	.18
3.9. More Information	. 19
Appendix A. Platform Requirements	20
Appendix B. Known Issues	. 21

LIST OF FIGURES

Figure 1	Nsight main window after creating a new project	. 8
Figure 2	Debugging CUDA application	10
Figure 3	Debugging remote CUDA application	18
Figure 4	Profiling CUDA Application	19

www.nvidia.com Nsight Eclipse Edition

Chapter 1. INTRODUCTION

This guide introduces Nsight Eclipse Edition and provides instructions necessary to start using this tool. For a detailed description of Nsight features consult the integrated help available from inside Nsight.

1.1. About Nsight Eclipse Edition

NVIDIA[®] Nsight[™] Eclipse Edition is a unified CPU plus GPU integrated development environment (IDE) for developing CUDA[®] applications on Linux and Mac OS X for the x86 and ARM platforms. It is designed to help developers on all stages of the software development process. Nsight Eclipse Edition is bundled in the NVIDIA CUDA Toolkit, so installing the CUDA Toolkit also installs Nsight. The principal features are as follows:

- Source editor with extended support for CUDA C and C++ syntax
- Projects and files management with version control management system integration. CVS and Git are supported out of the box with integrations for other systems available separately as IDE plug-ins.
- Configurable makefile-based NVCC build integration
- Graphical user interface for debugging heterogeneous applications
- Visual profiler with source code correlation for optimizing GPU code performance

Nsight Eclipse Edition is based on the popular Eclipse Platform and supports a wide range of the third-party extensions and plug-ins including:

- Version control management systems support
- Compiler integrations
- Language IDEs
- Application lifecycle management and collaboration solutions

For more information about Eclipse Platform, visit http://eclipse.org

Chapter 2. NEW AND NOTEWORTHY

2.1. New in Nsight Eclipse Edition 6.5

Stability release


Version 6.5 improves the stability of network connections to target systems and fixes an an occasional hang that could occur after profiling CUDA applications in earlier versions.

2.2. New in Nsight Eclipse Edition 6.0

Running Or Profiling Applications Remotely

In addition to remote debugging support introduced in Nsight Eclipse Edition 5.5, Nsight Eclipse Edition 6.0 is also able to run and profile applications on remote systems.

To run or profile on a remote system, select **Remote C/C++ Applicaton** from the dropdown on the main toolbar.



Building Projects On A Remote System

Nsight Eclipse Edition can now perform build on a remote system. Following actions will be performed:

- 1. Nsight will connect to a remote system and will synchronize copies of the project files between local and remote systems. User may be prompted to resolve conflicts if there are any.
- 2. *make* will be executed on a remote system to build the project.
- 3. Build results will be copied back to the local system.



Building project remotely requires *Git* to be available and set up on both the local and the remote system.

Target systems for remote build can be setup during project creation with the **New CUDA Project** wizard or on the **Build/Target Systems** project property page

😣 🗈 Properties for matrixmul			
type filter text	Target Systems	• • • •	
 Resource Build 	Select remote connection	Aanage	
Build Variables Discovery Options	Local System	×	
Environment	Project Path: //home/eostroukhov/cuda-workspace/matrixmul		
Settings	Toolkit: CUDA Toolkit 6.0 (/usr/local/cuda-6.0/bin/)		
Target Systems Tool Chain Editor	CPU Architecture: Native		
Builders	cudadeveloper@workstation	×	
 General Run/Debug Settings 	Project Path: /home/cudadeveloper/remote/matrixmul	Browse	
	Toolkit: /usr/local/cuda-6.0/bin	Manage	
	CPU Architecture: Native		
	Restore <u>D</u> efaults	Apply	
(?)	Cancel	ОК	

ARMv7 Cross Development Support

Nsight Eclipse Edition can now target Linux systems running on ARMv7 processors.



Please consult *CUDA Toolkit Release Notes* for information on enabling ARMv7 cross development support in CUDA Toolkit

CPU archicture for the project can be set during project creation with the **New CUDA Project** wizard or using the **Build/Target Systems** project property page

Local System		×
Project Path:	/home/eostrouk	hov/cuda-workspace/matrixmul
Toolkit:	CUDA Toolkit 6.0) (/usr/local/cuda-6.0/bin/)
CPU Architecture:	Native	
	ARM	
	x86 (32-Bit)	
	x86 (64-Bit)	

Cached And Extrapolated Values In Visual Debugger

cuda-gdb now reports cached and extrapolated values for variables in device code that were optimized out by the compiler.

🕬= Variables 🖾	<u>%</u>	** 🕞 🖇 🗶 📬 🗹 🖓	3
Name	Туре	T(1,11,0)B(5,1,0)	Â
(×)= ty	@register int	11	
⇔= aBegin	@register int	(cached) 10240	
⇔= aEnd	@register int	10559	
⇔• bBegin	@register int	(cached) 160	
(×)= bStep	@register int	20480	
(×)= Csub	float	0	
(×)= C	@register int	<optimized out=""></optimized>	E

2.3. New in Nsight Eclipse Edition 5.5

Remote Debugging Support

Nsight supports debugging CUDA applications running on remote systems. Nsight can both upload for debugging executable built locally and debug executable built remotely.

Kernel Launch Trace

Debug view now shows CDP launch trace.

CDP Project Support

CDP support can be enabled from a new project wizard during project creation or from project properties for existing projects.

Software Preemption Support

Software preeption debugging can be enabled from Nsight preferences.



Software preemption debugging is BETA and is only available on SM 3.5 and later devices. Consult cuda-gdb manual before enabling this setting.

Floating Point Memory Rendering

Floating-point rendering support was added to the memory view.

Remote System Explorer

Nsight Eclipse Edition now includes Remote System Explorer plug-in. This plugin enables accessing remote systems for file transfer, shell access and listing running processes.

Eclipse Platform Update

Nsight Eclipse Edition 5.5 is based on Eclipse Platform 3.8.2 and Eclipse CDT 8.1.2 introducing a number of new features and enhancements to existing features.

Chapter 3. USING NSIGHT ECLIPSE EDITION

3.1. Installing Nsight Eclipse Edition

Nsight Eclipse Edition is installed as a part of the CUDA Toolkit package.

3.1.1. Installing CUDA Toolkit

To install CUDA Toolkit:

- 1. Visit the NVIDIA CUDA Zone download page: http://www.nvidia.com/object/cuda_get.html
- **2.** Select appropriate operating system. Nsight Eclipse Edition is available in Mac OS X and Linux toolkit packages.
- 3. Download and install the CUDA Driver.
- 4. Download and install the CUDA Toolkit.
- 5. Follow instructions to configure CUDA Driver and Toolkit on your system.

3.1.2. Mac OS X Additional Notes

Nsight Eclipse Edition requires Java Runtime Environment (JRE) to be available on the local system. Compatible JRE is included in CUDA Toolkit package on Linux platform.

Mac OS X users need to have JDK 7 or later installed on their system, which can be downloaded from Oracle's Java website

Nsight Eclipse Edition relies on command-line development tools to be installed on the system. To install those command-line tools, Xcode must be installed first.

Once Xcode is installed, the command-line tools can be installed by running the following command:

```
$ xcode-select --install
```

Note: It is recommended to re-run the above command if Xcode is upgraded.

You can verify that the toolchain is installed by running the following command:

\$ /usr/bin/cc --version

3.2. Running Nsight Eclipse Edition

To run Nsight from the command line type

nsight

On Linux systems, Nsight is also available from Gnome, KDE and Unity desktop menus.

On the first run Nsight will ask to pick a workspace location. The workspace is a folder where Nsight will store its settings, local files history and caches. An empty folder should be selected to avoid overwriting existing files.

The main Nsight window will open after the workspace location is selected. The main window is divided into the following areas:

- *Editor* displays source files that are opened for editing.
- Project Explorer displays project files
- Outline displays structure of the source file in the current editor.
- *Problems* displays errors and warnings detected by static code analysis in IDE or by a compiler during the build.
- *Console* displays make output during the build or output from the running application.

3.3. Creating a New Project

- 1. From the main menu, open the new project wizard File > New... > CUDA C/C++ Project
- 2. Specify the project name and project files location.
- 3. Select CUDA Runtime Project to create a simple CUDA runtime application.
- 4. Specify the project parameters on the next wizard page.



By default Nsight will automatically detect and target CUDA hardware available locally. Nsight will default to SM 2.0 if no CUDA hardware is detected.

5. Complete the wizard.

The project will be shown in the **Project Explorer** view and source editor will be opened.

6. Build the project by clicking on the hammer button on the main toolbar.

	se /src/bitreverse.cu-Nsight or Navigate Search Project Run Window Help		
╡ ┇ ┇ ┙ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹ ╹	ऽग छे। छिग छेग ऐग ঔग ∫ ॐग Øग थु∎ग थु∎ग ∫ ॐ ∥ ∞ । ∭ ▣ ¶		Ê €C/C++
Image: Project E to a constraint of the second	<pre> bitreverse.cu ⊠ * Copyright 1993-2012 NVIDIA Corporation. All rights reserved.[#include <stdio.h> #include <stdio.h> static const int WORK_SIZE = 256; */** * This macro checks return value of the CUDA runtime call and exits * the application if the call failed. */ #define CUDA_CHECK_RETURN(value) {</stdio.h></stdio.h></pre>	2 1 nt	Image: Second state sta
	Writable Smart Insert 27:1		

Figure 1 Nsight main window after creating a new project

3.4. Importing CUDA Samples

The CUDA samples are an optional component of the CUDA Toolkit installation. Nsight provides a mechanism to import these samples and work with them easily:



Samples that use the CUDA driver API (suffixed with "Drv") are not supported by Nsight.

- From the main menu, open the new project wizard File > New... > CUDA C/C++ Project
- **2.** Specify the project name and project files location.
- 3. Select Import CUDA Sample under Executable in the Project type tree.
- 4. On the next wizard page select project sample you want to import. Press Next...
- 5. Specify the project parameters on the next wizard page.
- **6.** Complete the wizard.

The project will be shown in the **Project Explorer** view and source editor will be opened.

7. Build the project by clicking on the hammer button on the main toolbar.

3.5. Debugging CUDA Applications

Nsight must be running and at least one project must exist.

GPUs used to run X11 (on Linux) or Aqua (on Mac) cannot be used to debug CUDA applications in Nsight Eclipse Edition. Consult *cuda-gdb* documentation for details.

- **1.** In the **Project Explorer** view, select project you want to debug. Make sure the project executable is compiled and no error markers are shown on the project.
- 2. On the main window toolbar press Debug button (green bug).
- **3.** You will be offered to switch perspective when you run debugger for the first time. Click "Yes".

Perspective is a window layout preset specifically designed for a particular task.

- **4.** Application will suspend in the *main* function. At this point there is no GPU code running.
- 5. Add a breakpoint in the device code. Resume the application.

Debugger will break when application reaches the breakpoint. You can now explore your CUDA device state, step through your GPU code or resume the application.





Figure 2 Debugging CUDA application

3.6. Remote development of CUDA Applications


Nsight Eclipse Edition also supports remote development of CUDA application starting with CUDA Toolkit 6.0. The picture below shows how Nsight Eclipse Edition can be used for local as well as remote development:



For remote development you do not need any NVIDIA GPU on your host system. The remote target system can be a Linux desktop system with NVIDIA GPU or an ARM based Jetson TK1 system. Nsight IDE and UI tools are only available for x86 systems.

Nsight supports two remote development modes: the cross compilation mode and the remote synchronized project mode.


In the **cross compilation mode** the project resides on the host system and the cross compilation is also done on the host system. The cross compilation mode is only supported on Ubuntu x86 host system.



To cross compile select the target cross compile architecture in CPU architecture drop down:

Local System		×
Project Path:	/home/eostrouk	hov/cuda-workspace/matrixmul
Toolkit:	CUDA Toolkit 6.0) (/usr/local/cuda-6.0/bin/)
CPU Architecture:	Native	
	ARM	
	x86 (32-Bit)	
	x86 (64-Bit)	

In the **remote synchronized project mode** the project resides on the host system and gets synchronized with the remote target system. The compilation gets done natively on the target system. The remote synchronized project mode is supported on both Mac OS X and Linux x86 systems.



To create native remote build using **remote synchronized project mode** click on **Manage...** button to add a remote system, then select the project path, toolkit and the CPU architecture of the target system:

😣 🗈 Properties for matrixmul			
type filter text 🛛 🕱	Target Systems 🗢	• => • •	
 Resource Build 	Select remote connection \$	Manage	
Build Variables Discovery Options	Local System	×	
Environment Logging	Project Path: /home/eostroukhov/cuda-workspace/matrixmul Toolkit: CUDA Toolkit 6.0 (/usr/local/cuda-6.0/bin/)		
Settings Target Systems	CPU Architecture: Native		
Tool Chain Editor Builders	cudadeveloper@workstation	×	
 General Run/Debug Settings 	Project Path: /home/cudadeveloper/remote/matrixmul	Browse	
	Toolkit: /usr/local/cuda-6.0/bin	Manage	
	CPU Architecture: Native		
	Restore <u>D</u> efaults	<u>A</u> pply	
?	Cancel	ОК	

To synchronize projects between the host and target system, install and configure git on both the local and remote systems as follows:

```
git config --global user.name <anyname>
```


```
git config --global user.email <anyemail>
```

3.7. Debugging Remote CUDA Applications

Remote debugging is available starting with CUDA Toolkit 5.5. A dedicated GPU is not required to use Nsight remote debugging UI. A dedicated GPU is still required on the debug target. Only Linux targets are supported. Debug host and target may run different operating systems or have different CPU architectures. The remote machine must be accessible via SSH and CUDA Toolkit must be installed on both machines.

If there is a firewall between the host and the target, it must be set up to let RSP messages through, or SSH port-forwarding must be used.

1. Select Run>Debug an application menu item.



2. Select **Debug an application on a remote system** option.

😣 🗊 Debug CUDA Application	
Select Debug Session Type	
Select debug session type	
Debug an application on a remote system Remotely debug a CUDA application. This debug session can: 1. Copy debugged application executable to the the remote target. 2. Remotely launch cuda-gdbserver. 3. Connect to the remote server using local cuda-gdb Connect to cuda-gdbserver	
Connects to a running debug server	
Cancel Finish	

3. Type the full path to a local executable or select one using the **Local file...** button.

🗴 🗊 Debug CUDA Application			
Run cuda-gdbserve	r Remotely		
Opload local exection	utable O Debug remote executable	○ Do not transfer executable	
Local executable:	/home/test/bitreverse/bitreverse		
		Workspace Local File	
Remote connection:		New Edit	
Remote executable:	/tmp/nsight-debug/bitreverse	Browse	
Program arguments:			
cuda-gdbserver port:	2345 🗘		
?	< Back Next >	Cancel Finish	

- **4.** Select a remote connection from a drop-down list or press the **New...** button to create a new one.
- **5.** If you are creating a new remote connection, select the **SSH Only** connection type, press **Next**, and type the host name(or IP address) as well as the connection name and description (both are optional) and then press **Finish**.

🗧 🖲 New Connection	n
Remote SSH Only Sys	tem Connection
Define connection infor	mation
Parent profile:	debugger-host ‡
Host name:	debugger-target 💌
Connection name:	debugger-target
Description:	
Verify host name	<u>15</u>
?	< Back Next > Cancel Finish

- 6. Optional: Press **Connect** to verify the selected remote connection.
- 7. Press the Next button.
- **8.** Type the full path to cuda-gdbserver on the remote system or select one using the **Browse...** button.

🙁 🗊 🛛 Debug CUDA	Application	
Configure CUDA Too	olkits	
Configure CUDA tool	kit paths on the remote system	
cuda-gdbserver path:	/usr/local/cuda-5.5/bin/cuda-gdbserver	Browse
Library paths:	▷ /usr/local/cuda-5.5/lib	Browse
	🖶 Add new path	Delete
		£∎
Toolkit label:	CUDA-5.5]
(?)	< Back Next > Cancel	Finish

- **9.** Click on "Add new path" or on the **Browse...** button to specify the path to the shared libraries the remote application depends on.
- **10**Click on the **Finish** button to finish the new debug configuration wizard and start debugging the application.
- **11.**You will be offered to switch perspective when you run the debugger for the first time. Click **Yes**.

Perspective is a window layout preset specifically designed for a particular task.

The debugger will stop at the application main routine. You can now set breakpoints, or resume the application.

😣 🗐 🗊 Debug - /home/test/bitreverse/bitreverse.cu - Nsight								
X ■ Ⅱ ● ≠ [▲ ◎ ◎ □ · ↓ [▲ □ ■ Ⅱ ▲ [● ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓] 3. 🤊 .e i> 🗟 🕱] 🥭 🖋	▼ Ê ▼ "						
א Debug 🛚 🖈 🖓 א א א ו א ד ד ד ד	🕬= Variable 🕱 💊 Breakpo 📢 CU	JDA 🔤 Register 🛋 Modules 🗖 🗖						
▼	🔊 🏘 🖂 🖇 💥 📑 🗹 🎽							
 ▼ m Host Process [bitreverse] [cores: 0] ▼ m Thread [1] 10000 [core: 0] (Suspended : Breakpoint) 	Name Type	Value						
$\equiv main() at bitreverse.cu:40 0x4027d0$								
Remote Shell								
د bitreverse.cu ک	- 0	🗄 Outline 🕱 📃 🗖						
<pre>* Host function that prepares data array and passes it to the CUDA kernel. */ int main(void) { bitreverse<<<1, WORK_SIZE, WORK_SIZE * sizeof(int)>>>(); CUDA_CHECK_RETURN(cudaThreadSynchronize()); // Wait for the GPU launched work to com CUDA_CHECK_RETURN(cudaGetLastError()); CUDA_CHECK_RETURN(cudaDeviceReset()); return 0; }</pre>								
😑 Console 🕱 🖉 Tasks 🗄 Problems 📀 Executables 🔋 Memory 🛛 🖷 🛎 🐐 🗎 🚂 🖓 🖓 🛃 🖉 🖉 💌 😁 🔻 🗂 🖛								
bitreverse on debugger-target [C/C++ Remote Application] gdb Coalescing of the CUDA commands output is off.								
] 0*								

Figure 3 Debugging remote CUDA application

3.8. Profiling CUDA applications

Nsight must be running and at least one project must exist. Profiler cannot be used when debugging session is in progress.

Nsight Eclipse Edition profiling features are based on the NVIDIA Visual Profiler (*nvvp*) code. These two tools provide same features and have same user interface.

- **1.** In the **Project Explorer** view, select project you want to profile. Make sure the project executable is compiled and no error markers are shown on the project.
- 2. On the main window toolbar press the Profile button.
- 3. Press Yes when Nsight prompts to switch to the Profile perspective.

Nsight will switch to the **Profile** perspective and will display application execution timeline.

See Interview Profile - Timeline for session bitreverse - Nsight File Edit Navigate Search Project Run Window Help									
C⁺▼ 🔚 🐚 💩 🗞▼ 📾 Q₂▼ Q₂▼ A∕▼ A)▼ A)▼ ↔ ↔▼ ↔▼						🖺 🚱 Profile 🅸 🔭			
🖻 bitreverse.cu 🔍 *bitreverse 🛙 🗖					🔲 Prope 🕱 🗔 Detail 🗖 🗖				
							ef 🗸		
S		0.025 s	0.025 s 0.05 s 0.075 s 0.1 s				bitreverse(void*)		
Process 5688		1	1	1		Name	Value		
Thread -1455945920						Duration			
Runtime API	cudaMalloc cudaDeviceReset					Session	108.105 ms		
Driver API						Timeline	76.114 ms		
Profiling Overhead						Kernel	7.584 µs		
[0] GeForce GTX 280						Utilization	100%		
Context 1 (CUDA)						Invocations	1		
MemCpy (DtoH)							1		
Compute									
🍸 100.0% [1] bitrev									
 Streams 									
Stream 1									
		~							
🗔 Analysis 🛿 🗔 Details 💻	Consol	e							
Scope		esults							
Analyze Entire Application		Low Compute	Utilization [7.584	µs / 108.105 ms = 0%	5]		Â		
🔿 Analyze Kernel (select in tir	Analyze Kernel (select in timeline The multiprocessors of one or more GPUs are mostly idle.		-	Mo					
Stages Low Compute / Memcpy Efficiency [7.584 µs / 8.992 µs = 0.843] The amount of time performing compute is low relative to the amount of time performing compute			It of time required for memcpy. <u>Mo</u>						
Reset All Analyze A Timeline	Low Memcpy/Compute Overlap [0 ns / 7.584 µs = 0%] The percentage of time when memcpy is being performed in parallel with compute is low.								
Multiprocessor	Inefficient Memcpy Size								
∫ □◆									

Figure 4 Profiling CUDA Application

3.9. More Information

Some of the topics not covered in this guide are:

- Navigating debugged application state
- Enabling *cuda-memcheck* integration when debugging GPU applications
- Attaching to running applications
- Measuring GPU code efficiency
- ► Refactoring CUDA C/C++ source code
- Accessing CVS and Git repositories
- Installing Nsight Eclipse Edition plug-ins

More information about these and other topics is available in the Nsight built-in documentation. To access Nsight documentation select *Help->Help Contents* from the Nsight main menu.

More information about CUDA, CUDA Toolkit and other tools is available on CUDA web page at http://developer.nvidia.com/cuda

Appendix A. PLATFORM REQUIREMENTS

Nsight Eclipse Edition is supported on all Linux x86_64 versions and Mac OS X versions supported by the CUDA Toolkit.

A CUDA-capable GPU is not required for writing and compiling your CUDA application using Nsight Eclipse Edition. A CUDA-capable GPU is required for debugging and profiling CUDA applications. Debugging is supported on all CUDAcapable GPUs supported by the CUDA Toolkit.

A GPU that is running X11 (on Linux) or Aqua (on Mac) cannot be used to debug a CUDA application and will be hidden from the application ran in the debugger. Such GPU can still be used for profiling GPU applications.

Appendix B. KNOWN ISSUES

Executable must exist in order to start debug session for the first time

Nsight will not automatically perform build when starting debug session for a given project for the first time. Build must be invoked manually. Nsight will automatically rebuild executable when starting subsequent debug sessions.



To manually build the project, select it (or any file within the project) in a **Project Explorer** view and click hammer icon on the main window toolbar.

Source editors may show error markers on a valid code for the files in newly created projects.

These markers will be cleared after Nsight indexes included header files.

Mac OS X users may be prompted to install Java Runtime Environment (JRE) when running Nsight Eclipse Edition for the first time.

Nsight Eclipse Edition requires functioning Java Runtime Environment to be present on the local system to run.

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication of otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2007-2014 NVIDIA Corporation. All rights reserved.

